

TECHNICAL DATA SHEET

DOUBLE-SIDED TAPE

EAN code: 5907588403146 item no.: 0040065 type 6mm/5m
EAN code: 5907588403153 item no.: 0040066 type 9mm/5m
EAN code: 5907588403160 item no.: 0040067 type 12mm/5m
EAN code: 5907588403177 item no.: 0040068 type 15mm/5m
EAN code: 5907588403184 item no.: 0040069 type 19mm/5m
EAN code: 5907588420037 item no.: 0040060 type 6mm/10m
EAN code: 5907588410038 item no.: 0040061 type 9mm/10m
EAN code: 5907588400039 item no.: 0040062 type 12mm/10m
EAN code: 5907588460040 item no.: 0040063 type 15mm/10m
EAN code: 5907588400619 item no.: 0040064 type 19mm/10m



+ PROPERTIES

A double-sided adhesive tape ideal for securing moldings and decorative profiles in vehicles. It is resistant to salt, water, UV rays, and temperature fluctuations, offering high mechanical strength.

• COLOUR



dark green

⤵ METHOD OF USE

The tape is designed for use in automotive and industrial painting. The surface to which the tape is to be applied should be dry, dust-free and degreased.

+ PHYSICAL PROPERTIES

Medium:	polyethylene foam
Binder:	based on acrylic solvent
Total thickness:	935 µm
Medium thickness:	860 µm
Total weight:	200 g/m ²
Weight of backing:	76 g/m ²
Binder weight:	124 g/m ²
Adhesion to steel N/25mm:	17
Static shear:	>168h (1kg)
Tensile strength N/10cm:	15
Total elongation:	400%
Temperature strength:	from -20°C to +100°C
Temperature of use:	+13°C – +33°C

STORAGE



Protect the product from excessive low and high temperatures. Avoid direct exposure to sunlight. Store in dry places.

SHELF LIFE

12 months when stored in a dry place at 18°C - 21°C.

OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure its suitability for a specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specifications.