

## TECHNICAL DATA SHEET

### SELF-ADHESIVE ANTI-DRUMMING PANEL „FLEX”



**EAN code:** 5907588400084 item no.: 007000 dim. 50cm x 50cm

**EAN code:** 5907588404020 item no.: 0060109 dim. 25cm x 50cm

#### + PROPERTIES

Anti-drum panel “FLEX” is a very flexible self-adhesive soundproofing panel made of a mixture of bitumen, plasticizers, elastomers and fillers of different grain sizes. It is used in areas exposed to vibration. Particularly suitable for use in areas where high flexibility is required even at low temperatures.

#### • COLOUR

 black

#### + PHYSICAL PROPERTIES

|  |                             |
|--|-----------------------------|
| Density at 20°C:                           | 1,8 – 2,0 g/cm <sup>3</sup> |
| Weight:                                    | 1,5mm – 3,5mm               |
| Weight tolerance:                          | +/- 10%                     |
| Operating temperature:                     | -20°C / +80°C               |
| Storage temperature:                       | +10°C / +35°C               |
| Short term temperature resistance:         | 120°C                       |
| Burning speed (according to UNI ISO 3795): | <20mm/min                   |
| Flammability (according to FM VSS-302):    | class SE/NBR                |

#### ☞ STORAGE



Protect the product from excessive low and high temperatures. Avoid direct exposure to sunlight. Store in dry places.

#### ☰ OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure its suitability for a specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specifications.