

# ŚRODEK DO KONSERWACJI PODWOZIA NA PĘDZEL - UNDERBODY BRUSHABLE

ŚRODEK DO KONSERWACJI PODWOZIA NA PĘDZEL - UNDERBODY BRUSHABLE

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

# 1.1 Product identifier:

IIET-

# Other means of identification:

U4KW-S0RM-500N-1PVU

# 1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Agent for surface protection.

Uses advised against: All uses not specified in this section or in section 7.3

# 1.3 Details of the supplier of the safety data sheet:

BOLL Wojciech Dalewski Spółka Jawna ul. Chemiczna 3 65-713 Zielona Góra - Polska Phone: 68 451 99 99 - Fax: 68 451 99 00 huszcza@boll.pl https://www.boll.pl

# **1.4** Emergency telephone number:

# SECTION 2: HAZARDS IDENTIFICATION

# 2.1 Classification of the substance or mixture:

# CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

Eye Irrit. 2: Eye irritation, Category 2, H319

Flam. Lig. 3: Flammable liquids, Category 3, H226

Skin Irrit. 2: Skin irritation, Category 2, H315

STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2, H373

STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335

# 2.2 Label elements:

### CLP Regulation (EC) No 1272/2008:

Warning



### Hazard statements:

- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

### **Precautionary statements:**

P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P271: Use only outdoors or in a well-ventilated area.

P302+P352: IF ON SKIN: Wash with plenty of water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P314: Get medical advice/attention if you feel unwell.

P501: Dispose of contents/ container in accordance with local/regional/national/international regulation.

### Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking.

### Substances that contribute to the classification

Xylene; Hydrocarbons, C9, aromatics; Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics; Ethylbenzene



# SECTION 2: HAZARDS IDENTIFICATION (continued)

### UFI: U4KW-S0RM-500N-1PVU

The product packaging must include: tactile warning.

### 2.3 Other hazards:

Product does not meet PBT/vPvB criteria

Endocrine-disrupting properties: The product does not meet the criteria.

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substance:

Non-applicable

### 3.2 Mixture:

Chemical description: a mixture of hydrocarbons and ethanol

### Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification	Concentration
CAS:	1330-20-7	Xylene <sup>(1)</sup>	Self-classified	1
EC: Index: REACH:	215-535-7 601-022-00-9 : 01-2119488216-32- XXXX	Regulation 1272/2008	Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	9,7 - <12,7 %
EC: Index: REACH:	128601-23-0	Hydrocarbons, C9, ai	romatics <sup>(1)</sup> Self-classified	1
	918-668-5 Non-applicable 01-2119455851-35- XXXX	Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: 4335; STOT SE 3: H336; EUH066 - Danger	8 - <10,9 %
CAS:	Non-applicable 919-857-5 Non-applicable : 01-2119463258-33- XXXX	Hydrocarbons, C9-C1	L1,n-alkanes, iso-alkanes, cyclics, <2% aromatics <sup>(1)</sup> Self-classified	1
EC: Index: REACH:		Regulation 1272/2008	Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Danger 🔅 🗘 🔇	2 - <3 %
CAS:	100-41-4	Ethylbenzene <sup>(1)</sup>	ATP ATP06	
EC: Index: REACH:	202-849-4 601-023-00-4 : 01-2119489370-35- XXXX	Regulation 1272/2008	Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger	1,3 - <1,6 %

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acut	te toxicity	Genus
Xylene	LD50 oral	Not relevant	
CAS: 1330-20-7	LD50 dermal	1100 mg/kg	Rat
EC: 215-535-7	LC50 inhalation	11 mg/L (ATEi)	

# SECTION 4: FIRST AID MEASURES

# 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product. **By inhalation:** 

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance. **By skin contact:** 



# SECTION 4: FIRST AID MEASURES (continued)

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

### By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

### By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

# 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

### 4.3 Indication of any immediate medical attention and special treatment needed:

Not available

### SECTION 5: FIREFIGHTING MEASURES

### 5.1 Extinguishing media:

# Suitable extinguishing media:

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

### Unsuitable extinguishing media:

Water jet

### 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

### 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

# Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures:

### For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

### For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

# 6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

# 6.3 Methods and material for containment and cleaning up:



# ŚRODEK DO KONSERWACJI PODWOZIA NA PĘDZEL - UNDERBODY BRUSHABLE

# SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

### 6.4 Reference to other sections:

See sections 8 and 13.

# SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

### 7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.:	10 °C
Maximum Temp.:	20 °C
Maximum time:	24 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

### 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Version: 1

### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
(ylene <sup>(1)</sup>	IOELV (8h)	50 ppm	221 mg/m <sup>3</sup>
CAS: 1330-20-7 EC: 215-535-7	IOELV (STEL)	100 ppm	442 mg/m <sup>3</sup>
Ethylbenzene (1)	IOELV (8h)	100 ppm	442 mg/m <sup>3</sup>
CAS: 100-41-4 EC: 202-849-4	IOELV (STEL)	200 ppm	884 mg/m <sup>3</sup>

<sup>(1)</sup> Skin



# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

# **DNEL (Workers):**

		Short	exposure	Long	exposure
Identification		Systemic	Local	Systemic	Local
Xylene	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 1330-20-7	Dermal	Not relevant	Not relevant	212 mg/kg	Not relevant
EC: 215-535-7	Inhalation	442 mg/m <sup>3</sup>	442 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>
Hydrocarbons, C9, aromatics	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 128601-23-0	Dermal	Not relevant	Not relevant	25 mg/kg	Not relevant
EC: 918-668-5	Inhalation	Not relevant	Not relevant	150 mg/m <sup>3</sup>	Not relevant
Ethylbenzene	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 100-41-4	Dermal	Not relevant	Not relevant	180 mg/kg	Not relevant
EC: 202-849-4	Inhalation	Not relevant	293 mg/m <sup>3</sup>	77 mg/m <sup>3</sup>	Not relevant

# **DNEL (General population):**

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Xylene	Oral	Not relevant	Not relevant	12,5 mg/kg	Not relevant
CAS: 1330-20-7	Dermal	Not relevant	Not relevant	125 mg/kg	Not relevant
EC: 215-535-7	Inhalation	260 mg/m <sup>3</sup>	260 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>
Hydrocarbons, C9, aromatics	Oral	Not relevant	Not relevant	11 mg/kg	Not relevant
CAS: 128601-23-0	Dermal	Not relevant	Not relevant	11 mg/kg	Not relevant
EC: 918-668-5	Inhalation	Not relevant	Not relevant	32 mg/m <sup>3</sup>	Not relevant
Ethylbenzene	Oral	Not relevant	Not relevant	1,6 mg/kg	Not relevant
CAS: 100-41-4	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
EC: 202-849-4	Inhalation	Not relevant	Not relevant	15 mg/m <sup>3</sup>	Not relevant

PNEC:

Identification				
Xylene	STP	6,58 mg/L	Fresh water	0,327 mg/L
CAS: 1330-20-7	Soil	2,31 mg/kg	Marine water	0,327 mg/L
EC: 215-535-7	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Not relevant	Sediment (Marine water)	12,46 mg/kg
Ethylbenzene	STP	9,6 mg/L	Fresh water	0,1 mg/L
CAS: 100-41-4	Soil	2,68 mg/kg	Marine water	0,01 mg/L
EC: 202-849-4	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg
	Oral	0,02 g/kg	Sediment (Marine water)	1,37 mg/kg

#### 8.2 **Exposure controls:**

A.- Individual protection measures, such as personal protective equipment

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have CE marking in accordance with Directive 2016/425/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

### B.- Respiratory protection

Filter mask for gases and CE EN 405:	Replace when there is a taste or smell of the
Mandatory respiratory tract protection	2002+A1:2010 contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.-



Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)		EN ISO 21420:2020	Replace the gloves at any sign of deteric
	a mixture of several sub- nd has therefore to be che			rial can not be calculated in advance
D Eye and face pro		1		
Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Face shield		EN 166:2002 UNE-EN ISO 18526-1 al 4:2020 UNE-EN ISO 18526-1 al 4:2020 EN ISO 4007:2018	Clean daily and disinfect periodically acco the manufacturer's instructions. Use if th risk of splashing.
E Body protection				
Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	CAT III	EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982- 1:2005/A1:2011 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1995	For professional use only. Clean period according to the manufacturer's instruc
Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		EN ISO 13287:2020 EN ISO 20345:2022 EN 13832-1:2019	Replace boots at any sign of deteriora
F Additional emerg	ency measures			
Emergency me	asure S	standards	Emergency measu	ire Standards
Emergency sh	ISO 3864-1:20	ISI Z358-1 011, ISO 3864-4:20	11 Eyewash station	DIN 12 899 ISO 3864-1:2011, ISO 3864-4: s
Environmental ex	posure controls:		•	
spillage of both the p Volatile organic co	product and its container.	For additional i	nformation see subsectior	s recommended to avoid environme 1 7.1.D
V.O.C. (Supply):	26,9	1 % weight		
V.O.C. density at		kg/m³ (342 g/L	.)	
Average carbon i				
Average molecul	ar weight: 115,2	71 g/mol		
	AND CHEMICAL PROP	PERTIES		
ON 9: PHYSICAL		ical properties	5:	
Information on ba	sic physical and chem			
<b>Information on ba</b> For complete informa	ation see the product dat			
Information on ba	ation see the product dat	asheet.		
<b>Information on ba</b> For complete informa	ation see the product dat			



SECI	FION 9: PHYSICAL AND CHEMICAL PROPERTIE	ES (continued)
	Colour:	Black
	Odour:	Characteristic
	Odour threshold:	Not available *
	Volatility:	
	Boiling point at atmospheric pressure:	150 °C
	Vapour pressure at 20 °C:	300 Pa
	Vapour pressure at 50 °C:	Not available *
	Evaporation rate at 20 °C:	Not available *
	Product description:	
	Density at 20 °C:	1300 kg/m³
	Relative density at 20 °C:	1,3
	Dynamic viscosity at 20 °C:	Not available *
	Kinematic viscosity at 20 °C:	Not available *
	Kinematic viscosity at 40 °C:	>20,5 mm²/s
	Concentration:	Not available *
	pH:	Not available *
	Vapour density at 20 °C:	Not available *
	Partition coefficient n-octanol/water 20 °C:	Not available *
	Solubility in water at 20 °C:	Not available *
	Solubility properties:	Not available *
	Decomposition temperature:	Not available *
	Melting point/freezing point:	Not available *
	Flammability:	
	Flash Point:	32 °C
	Flammability (solid, gas):	Not available *
	Autoignition temperature:	Not available *
	Lower flammability limit:	0,7 % Volume
	Upper flammability limit:	7 % Volume
	Particle characteristics:	
	Median equivalent diameter:	Non-applicable
9.2	Other information:	
	Information with regard to physical hazard cla	
	Explosive properties:	Not available *
	Oxidising properties:	Not available *
	Corrosive to metals:	Not available *
	Heat of combustion:	Not available *
	Aerosols-total percentage (by mass) of flammable components: Other safety characteristics:	Not available *
	Surface tension at 20 °C:	Not available *
	Refraction index:	Not available *
	*Not available due to the nature of the product, not providing in	formation property of its hazards.

# SECTION 10: STABILITY AND REACTIVITY

Version: 1

10.1 Reactivity:



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

# ŚRODEK DO KONSERWACJI PODWOZIA NA PĘDZEL - UNDERBODY BRUSHABLE

### SECTION 10: STABILITY AND REACTIVITY (continued)

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

# 10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

### **10.4** Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

### 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

# **10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide ( $CO_2$ ), carbon monoxide and other organic compounds.

# SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
  - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
  - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
  - Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
  - Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Produces skin inflammation.
  - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
  - IARC: Xylene (3); Hydrocarbons, C9, aromatics (3); Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics (3); Ethylbenzene (2B)
  - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
  - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
  - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.



# ŚRODEK DO KONSERWACJI PODWOZIA NA PĘDZEL - UNDERBODY BRUSHABLE

# SECTION 11: TOXICOLOGICAL INFORMATION (continued)

F- Specific target organ toxicity (STOT) - single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

- Skin: Repeated exposure may cause skin dryness or cracking
- H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

### Other information:

### Not relevant

### Specific toxicology information on the substances:

Identification	A	Acute toxicity	
Xylene	LD50 oral	2100 mg/kg	Rat
CAS: 1330-20-7	LD50 dermal	1100 mg/kg (ATEi)	Rat
EC: 215-535-7	LC50 inhalation	11 mg/L (ATEi)	
Hydrocarbons, C9, aromatics	LD50 oral	>2000 mg/kg	
CAS: 128601-23-0	LD50 dermal	>2000 mg/kg	
EC: 918-668-5	LC50 inhalation	>20 mg/L	
Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics	LD50 oral	>5000 mg/kg	Rat
CAS: Non-applicable	LD50 dermal	>2000 mg/kg	
EC: 919-857-5	LC50 inhalation	>20 mg/L	
Ethylbenzene	LD50 oral	3500 mg/kg	Rat
CAS: 100-41-4	LD50 dermal	15354 mg/kg	Rabbit
EC: 202-849-4	LC50 inhalation	17,2 mg/L (4 h)	Rat

# **11.2** Information on other hazards:

# Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Version: 1

### **Other information**

Not relevant

# SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Harmful to aquatic life with long lasting effects.

# 12.1 Toxicity:

### Acute toxicity:

Identification		Concentration	Species	Genus	
Xylene	LC50	>10 - 100 mg/L (96 h)		Fish	
CAS: 1330-20-7	EC50	>10 - 100 mg/L (48 h)		Crustacean	
EC: 215-535-7	EC50	>10 - 100 mg/L (72 h)		Algae	
Hydrocarbons, C9, aromatics	LC50	>1 - 10 mg/L (96 h)		Fish	
CAS: 128601-23-0	EC50	>1 - 10 mg/L (48 h)		Crustacean	
EC: 918-668-5	EC50	>1 - 10 mg/L (72 h)		Algae	
Ethylbenzene	LC50	42,3 mg/L (96 h)	Pimephales promelas	Fish	
CAS: 100-41-4	EC50	75 mg/L (48 h)	Daphnia magna	Crustacean	
EC: 202-849-4	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae	



# ŚRODEK DO KONSERWACJI PODWOZIA NA PĘDZEL - UNDERBODY BRUSHABLE

SECT	ION 12: ECOLOGICAL INFORMATION (continue	ed)			
	Identification		Concentration	Species	Genus
	Xylene	NOEC	1,3 mg/L	Oncorhynchus mykiss	Fish
	CAS: 1330-20-7 EC: 215-535-7	NOEC	1,17 mg/L	Ceriodaphnia dubia	Crustacean
	Ethylbenzene	NOEC	Not relevant		
	CAS: 100-41-4 EC: 202-849-4	NOEC	0,96 mg/L	Ceriodaphnia dubia	Crustacean
12.2	Persistence and degradability:				

# Substance-specific information:

Identification	Degradability		Biodegradability	
Xylene	BOD5	Not relevant	Concentration	Not relevant
CAS: 1330-20-7	COD	Not relevant	Period	28 days
EC: 215-535-7	BOD5/COD	Not relevant	% Biodegradable	88 %
Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics	BOD5	Not relevant	Concentration	Not relevant
CAS: Non-applicable	COD	Not relevant	Period	28 days
EC: 919-857-5	BOD5/COD	Not relevant	% Biodegradable	80 %
Ethylbenzene	BOD5	Not relevant	Concentration	100 mg/L
CAS: 100-41-4	COD	Not relevant	Period	14 days
EC: 202-849-4	BOD5/COD	Not relevant	% Biodegradable	90 %

# **12.3** Bioaccumulative potential:

### Substance-specific information:

Identification	Bioaccumulation potential		
Xylene	BCF	9	
CAS: 1330-20-7	Pow Log	2.77	
EC: 215-535-7	Potential	Low	
Ethylbenzene	BCF	1	
CAS: 100-41-4	Pow Log	3.15	
EC: 202-849-4	Potential	Low	

# 12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Xylene	Кос	202	Henry	524,86 Pa·m <sup>3</sup> /mol
CAS: 1330-20-7	Conclusion	Moderate	Dry soil	Yes
EC: 215-535-7	Surface tension	Not relevant	Moist soil	Yes
Ethylbenzene	Кос	520	Henry	798,44 Pa·m³/mol
CAS: 100-41-4	Conclusion	Moderate	Dry soil	Yes
EC: 202-849-4	Surface tension	2,859E-2 N/m (25 °C)	Moist soil	Yes

# 12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

# 12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

# 12.7 Other adverse effects:

Not described

# SECTION 13: DISPOSAL CONSIDERATIONS

# 13.1 Waste treatment methods:

# Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):



# SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

# **Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

# SECTION 14: TRANSPORT INFORMATION

### Transport of dangerous goods by land: With regard to ADR 2023 and RID 2023: 14.1 UN number or ID number: UN1139 14.2 UN proper shipping name: COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle under coating, drum or barrel lining) 14.3 Transport hazard class(es): 3 Labels: 3 14.4 Packing group: III 14.5 Environmental hazards: No 14.6 Special precautions for user Special regulations: Not relevant Tunnel restriction code: D/E Physico-Chemical properties: see section 9 Limited quantities: 51 14.7 Maritime transport in bulk Not relevant according to IMO instruments: Transport of dangerous goods by sea: With regard to IMDG 41-22: 14.1 UN number or ID number: UN1139 14.2 UN proper shipping name: COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle under coating, drum or barrel lining) 14.3 Transport hazard class(es): 3 Labels: 3 14.4 Packing group: III 14.5 Marine pollutant: No 14.6 Special precautions for user 955 Special regulations: EmS Codes: F-E, S-E Physico-Chemical properties: see section 9 Limited quantities: 5 L Not relevant Segregation group: 14.7 Maritime transport in bulk Not relevant according to IMO instruments: Transport of dangerous goods by air: With regard to IATA/ICAO 2024:



# ŚRODEK DO KONSERWACJI PODWOZIA NA PĘDZEL - UNDERBODY BRUSHABLE

SECTION 14: TRANSF	PORT	INFORMATION (continued)	
		UN number or ID number: UN proper shipping name:	UN1139 COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle under coating, drum or barrel lining)
3	14.3	Transport hazard class(es): Labels:	3 3
		Packing group:	III
		Environmental hazards: Special precautions for user	No
		Physico-Chemical properties:	see section 9
	14.7	Maritime transport in bulk according to IMO instruments:	Not relevant

# SECTION 15: REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Article 95, REGULATION (EU) No 528/2012: Not relevant
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Not relevant
- Regulation (EU) No 2024/590, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

### Seveso III:

	Section	Description	Lower-tier requirements	Upper-tier requirements
	P5c	FLAMMABLE LIQUIDS	5000	50000
1.1	l imitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII PEACH			

cialisation and the use of certain dangerous substances and mixtu etc ....):

Shall not be used in:

-ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

# Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

# Other legislation:

The product could be affected by sectorial legislation

# 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.


# SECTION 16: OTHER INFORMATION

## Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

### Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.: Not relevant

Texts of the legislative phrases mentioned in section 2:



BOLL

# ŚRODEK DO KONSERWACJI PODWOZIA NA PĘDZEL - UNDERBODY BRUSHABLE

CTIC	ON 16: OTHER INFORMATION (continued)
Н	226: Flammable liquid and vapour.
	315: Causes skin irritation.
	319: Causes serious eye irritation.
	335: May cause respiratory irritation.
	373: May cause damage to organs through prolonged or repeated exposure.
	412: Harmful to aquatic life with long lasting effects.
	exts of the legislative phrases mentioned in section 3:
	he phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the
	dividual components which appear in section 3
С	LP Regulation (EC) No 1272/2008:
Α	cute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.
	cute Tox. 4: H332 - Harmful if inhaled.
	quatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
	quatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
	sp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
	ye Irrit. 2: H319 - Causes serious eye irritation. Iam. Liq. 2: H225 - Highly flammable liquid and vapour.
	lam. Liq. 3: H226 - Flammable liquid and vapour.
	kin Irrit. 2: H315 - Causes skin irritation.
	TOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).
	TOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.
	TOT SE 3: H335 - May cause respiratory irritation.
S	TOT SE 3: H336 - May cause drowsiness or dizziness.
С	lassification procedure:
F	lam. Liq. 3: Calculation method (2.6.4.3)
-	kin Irrit. 2: Calculation method
	ye Irrit. 2: Calculation method
	TOT SE 3: Calculation method
	TOT RE 2: Calculation method quatic Chronic 3: Calculation method
	dvice related to training:
	-
	raining is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension an Iterpretation of this safety data sheet, as well as the label on the product.
P	rincipal bibliographical sources:
h	ttp://echa.europa.eu
	ttp://eur-lex.europa.eu
A	bbreviations and acronyms:
	DR: European agreement concerning the international carriage of dangerous goods by road
	MDG: International maritime dangerous goods code
	ATA: International Air Transport Association
	CAO: International Civil Aviation Organisation
	OD: Chemical Oxygen Demand
	OD5: 5day biochemical oxygen demand
	CF: Bioconcentration factor
	D50: Lethal Dose 50
	C50: Lethal Concentration 50 C50: Effective concentration 50
	ogPOW: Octanolwater partition coefficient
	oc: Partition coefficient of organic carbon
	FI: unique formula identifier
	ARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -