

DEFLECTING TAPE 2IN1



EAN code: 5907588400947 item no.: 004016 type 50mm/10m



PROPERTIES

Tape used to mask the seals of the inserted window panes. Plastic belt enables easy placement of the tape under the seal. It facilitates access to places between the seal and car body. It comes in a roll, 10 m long, 50 mm wide, and two plastic strips: 9 and 11 mm wide.



COLOUR

 yellow



METHOD OF USE

The surface on which the tape is to be applied should be dry, dust-free and degreased. Tear off the required piece of tape along the perforation and insert it with the plastic strip side into the gap between the seal and the window recess. While gently pulling on the tape, lift the edge of the seal. Mask the rest of the surface with paper or foil.



PHYSICAL PROPERTIES

Carrier:	low stabilized crepe paper
Thickness:	0,30 mm
Adhesive base:	cross-linked modified rubber
Peel strength:	10 N/25 mm
Heat resistance:	up to 150°C/1h
Weather resistance:	limited
Core diameter:	76 mm
Special data:	resistant to water-based varnish



STORAGE CONDITION



Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.



SHELF LIFE

The varnish tape stored in a dry place at 18 ° C and 55% relative humidity retains its properties for 12 months.



OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.