


TECHNICAL DATA SHEET

STRUCTURE LACQUER FOR PLASTIC







+

PROPERTIES

Structural lacquer for plastic is a fast-drying and well-bonding paint based on acrylic resins. It is ideal for painting plastic bumpers, moldings and other plastic parts with a spray gun. It forms an attractive structural, durable coating in black or dark gray matte. The paint can be applied directly without primer to all plastic surfaces.



COLOUR



grey



black



APPLICATION



Thoroughly clean and mat the surface



Thoroughly clean and degrease the surface with "BOLL Silicon remover"



Mix thoroughly



Use a maximum 5 - 10% of "BOLL Acrylic thinner"



Nozzle: 1,5 - 2,0 mm Pressure: 1,8 - 2,5 bar Number of layers: 2 - 3



Time between layers: 5 – 10 minutes



Drying time around 6 hours at 20°C





Can be painted

#

PHYSICAL PROPERTIES

Temperature of application:

+15°C - +25°C



STORAGE







Protect the product from excessive low and high temperatures. Avoid direct exposure to sunlight. Store in dry places.

置

SHELF LIFE

Two years from the production date placed on the package.

!

SAFETY

See Safety Data Sheet.



OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure its suitability for a specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specifications.