

TECHNICAL DATA SHEET

QUICK-DRYING PRIMER PAINT SPRAY

EAN code: 5907588407922 item no.: 0010210 white

EAN code: 5907588402545 item no.: 001020 beige

EAN code: 5907588410007 item no.: 001021 grey

EAN code: 5907588403641 item no.: 0010199 black



+ PROPERTIES

The quick-drying primer paint is ideal for preparing the substrate in paint jobs on car body parts. It has excellent rust protection properties and is highly scratch resistant, making it a very good substrate before applying paint. Easy to work with, it does not cause sandpaper clogging. It can be coated with acrylic, alkyd, cellulose and epoxy paints.

• COLOUR



= SURFACE

- metal** - sand, blow off and degrease with "BOLL Silicon remover", then apply another coat.
- non-ferrous metals (zinc, aluminium, cooper, etc.)** - prime, sand, blow off and degrease with "BOLL Silicon remover", then apply another coat.
- old primer coatings** - sand with P240 - P320 paper, blow off, degrease with "BOLL Silicon remover", and then apply another coat.
- epoxy primer** - can be used to isolate materials. After sanding, blow off, degrease with "BOLL Silicon remover", and then apply another coat.
- two-component acrylic primer** - sand, blow off, degrease with "BOLL Silicon remover", and then apply another coat.
- polyester putties** - sand, blow off and degrease with "BOLL Silicon remover", and then apply another coat.

APPLICATION



Thoroughly clean and mat the surface



Thoroughly clean and degrease the surface with BOLL Silicon remover



Mix thoroughly



Apply 2-3 layers from a distance of 15-20 cm



Time between layers: 5 – 10 minutes



After about 1 hour, the surface can be coated with varnish



After use, turn the container over and spray until the valve is empty

PHYSICAL PROPERTIES

Physical state: aerosol
Temperature of use: +18°C – +25°C

STORAGE



Protect the product from excessive low and high temperatures. Avoid direct exposure to sunlight. Store in dry places.

SHELF LIFE

Two years from the production date placed on the package.

SAFETY

See Safety Data Sheet.

OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure its suitability for a specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specifications.