

TECHNICAL DATA SHEET ZINK SPRAY

EAN code: 5907588402781 item no.: 0010211 grey



+ PROPERTIES

Zinc spray is a fast-drying agent that provides excellent corrosion protection for steel structures, body and chassis components and all kinds of piping systems. It allows electrical welding of coated surfaces. It has excellent adhesion and flexibility, forming a smooth coating that provides thorough protection for all types of paint. Resistant to temperatures up to 120°C. Excellent as a primer for surfaces exposed to moisture. Once dry, it can be varnished. Zinc content in the dry layer is 90%. The product conforms to DIN standards.

• COLOUR



grey

/// APPLICATION



Thoroughly clean and mat the surface



Thoroughly clean and degrease the surface with "BOLL Silicon remover"



Mix thoroughly



Numbers of layers: 1 – 2
distance 15 – 20 cm



Time between layers: 5 – 10 minut



Drying time 24 hours



After use, turn the container over and spray until the valve is empty

PHYSICAL PROPERTIES

Physical state:	aerosol
Zinc content by weight in dry matter:	90%
Temperature of use:	+18°C – +25°C

STORAGE



Protect the product from excessive low and high temperatures. Avoid direct exposure to sunlight. Store in dry places.

SHELF LIFE

Two years from the production date placed on the package.

SAFETY

See Safety Data Sheet.

OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure its suitability for a specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specifications.