

## TECHNICAL DATA SHEET

### CAVITY WAX

EAN code: 5907588402972 item no.: 0010101 white

EAN code: 5907588470018 item no.: 001009 amber



#### + PROPERTIES

Extremely effective wax-based agent for corrosion protection of closed car body sections (e.g. bonnet, sills or doors). Forms a tight and flexible coating to protect against water, salt and rust. Available in two colours: white and amber. **The amber agent** has a lower viscosity, making it more penetrating - it reaches the depths of the profiles more easily. **White agent** (with higher viscosity): is better suited, for example, to protect the inner surfaces of door sheets or bonnets, as it leaves a thicker layer after application that does not run off. Many professionals use both agents - one after the other (amber and then white).

#### • COLOUR



white



amber

#### ☰ INFORMATION

The agent should be injected into existing holes in the car body using a spray gun equipped with a suitable adapter. If necessary, drill holes with a diameter of 6 mm.


#### /// APPLICATION



Mix thoroughly



Inject with a spray gun equipped with a suitable adapter  
Pressure 4 - 6 bar



Recommended coating thickness from 0,2 mm to 0,4 mm



Drying time approx. 4 hours

## PHYSICAL PROPERTIES

Density at 20°C:	0,813 - 0834 g/cm <sup>3</sup>
Temperature of application:	+15°C – +25°C

## CLEANING

Wash the gun with white spirit.

## STORAGE



Protect the product from excessive low and high temperatures. Avoid direct exposure to sunlight. Store in dry places.

## SHELF LIFE

Two years from date placed on the package.

## SAFETY

See Safety Data Sheet.

## OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure its suitability for a specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specifications.