

BOLL

TECHNICAL DATA SHEET PLASTIC PRIMER SPRAY



EAN code: 5907588403245 item no.: 0010122

PROPERTIES +

Single-component quick drying priming spray that increases adhesion between the plastic surface and the varnish layer. Due to its flexibility it is used as a primer before painting plastic car parts such as bumpers, spoilers, etc.



COLOUR

colourless

INFORMATION

Do not use on heated plastic parts.

APPLICATION	
M	Thoroughly clean and matt the surface
	Thoroughly clean and degrease the surface with BOLL Silicon remover
3min.	Mix thoroughly
15-20 cm 2-3x	Apply 2 – 3 layers from a distance of 15 – 20 cm
	Time between layers: 5 – 10 minutes
45 min. 20°C	After about 45 minutes, the surface can be painted





After use, turn the container over and spray until the valve is empty

+ PHYSICAL PROPERTIES

Physical state: Temperature of application: aerosol +15°C - +25°C

STORAGE



Protect the product from excessive low and high temperatures. Avoid direct exposure to sunlight. Store in dry places.

🛗 SHELF LIFE

Two years from the date placed on the package.

SAFETY

See Safety Data Sheet.

OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure its suitability for a specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specifications.