

TECHNICAL DATA SHEET SPRAY BOOTH PROTECTIVE LIQUID

POST IN EXPENSES

EAN code: 5907588403375 item no.: 0030031 cap. 5 l



PROPERTIES

Cabin fluid is a transparent, odorless liquid used in spray booths. It forms a coating that attracts and retains dust and dirt. It is used on walls, ceiling, suction channels, lighting equipment, etc. in paint booths.

The time of adhesion to the surface is about 3 months.



COLOUR

colourless



METHOD OF USE

Apply the liquid to the desired surfaces in the spray booth using a spray gun, roller or brush. The product is suitable for direct use. If necessary, it can also be diluted with water. After the adhesion time, remove by washing with water.



PHYSICAL PROPERTIES

Density at 20°C:

1,079 g/cm³ 7 – 8

pH:

water-soluble

mixture containing glycerin and adhesion agents



STORAGE







Należy chronić produkt przed zbyt niskimi i wysokimi temperaturami. Unikać bezpośredniego naświetlania promieniami słonecznymi. Przechowywać w suchych miejscach.





SHELF LIFE

Two years from the date placed on the package.

!

SAFETY

See Safety Data Sheet.

OTHER INFROMATION

All technical data are approximate values. We advise you to test the material to ensure its suitability for a specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specifications.