

TECHNICAL DATA SHEET

ANTICORROSIVE PRIMING PAINT SPRAY




EAN code: 5907588403764 item no.: 001408 cap. 500ml

+ PROPERTIES

Primer paint for substrate preparation and long-term corrosion protection of car body parts. It is mainly used in paint work, but is also used in industry or construction. It forms a smooth protective coating highly resistant to abrasion, water, including salt water, gasoline and most aggressive chemicals. Resistant to corrosion according to DIN 50021 and the effects of high temperatures (short-term up to +140°C in dry conditions and +80°C in wet conditions).

• COLOUR



oxide red

= SURFACE

- **metal** – sand, blow off and degrease with “BOLL Silicon Remover”, and then apply another coat.
- **non-ferrous metals (zinc, aluminum, copper, etc.)** – prime, sand, blow off and degrease with “BOLL Silicon remover”, and then apply another coat.
- **old paint coatings** – sand with P240 - P320 paper, blow off, degrease with “BOLL Silicon remover”, and then apply another coat.
- **polyester putty** – sand, blow off and degrease with “BOLL silicone remover”, and then apply another coat.






/// APPLICATION



Thoroughly clean and mat the surface






Thoroughly clean and degrease the surface with BOLL Silicon remover

	Mix thoroughly
	Apply 2 – 3 layers from a distance of 15 – 20 cm
	Time between layers: 5 – 10 minutes
	After about 24 hours, the surface can be covered by most paints and varnishes
	After use, turn the container over and spray until the valve is empty

PHYSICAL PROPERTIES

Physical state:	aerosol
Drying time:	depending on layer thickness, ambient temperature and ventilation
Temperature of use:	+18°C – +25°C

STORAGE

		
---	---	---

Protect the product from excessive low and high temperatures. Avoid direct exposure to sunlight. Store in dry places.

SHELF LIFE

Two years from the date placed on the package.

SAFETY

See Safety Data Sheet.



OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure its suitability for a specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specifications.