

TECHNICAL DATA SHEET

DOUBLE-SIDED ACRYLIC TAPE


EAN code: 5907588405423 **item no.:** 0040076 **type** 6mm/5m
EAN code: 5907588405430 **item no.:** 0040077 **type** 9mm/5m
EAN code: 5907588405447 **item no.:** 0040078 **type** 12mm/5m
EAN code: 5907588405454 **item no.:** 0040079 **type** 15mm/5m
EAN code: 5907588405461 **item no.:** 0040081 **type** 19mm/5m
EAN code: 5907588405314 **item no.:** 0040071 **type** 6mm/10m
EAN code: 5907588405324 **item no.:** 0040072 **type** 9mm/10m
EAN code: 5907588405331 **item no.:** 0040073 **type** 12mm/10m
EAN code: 5907588405348 **item no.:** 0040074 **type** 15mm/10m
EAN code: 5907588405355 **item no.:** 0040075 **type** 19mm/10m



+ PROPERTIES

A double-sided adhesive tape ideal for securing moldings and decorative profiles in vehicles. It is resistant to salt, water, UV rays, and temperature fluctuations, offering high mechanical strength.

• COLOUR



☞ METHOD OF USE

The tape is designed for use in automotive and industrial painting. The surface to which the tape is to be applied should be dry, dust-free and degreased.

☰ INFORMATION

The tape reaches its proper technical parameters after 24 hours at a temperature of approx. 20°C. Do not stretch the tape during application as it will lose its technical properties when returning to its original dimensions.



PHYSICAL PROPERTIES

Medium:	acrylic
Binder:	acrylic
Total thickness:	0,85 mm
Medium thickness:	0,8 mm
Tape colour:	grey
Medium colour:	red
Breaking strength N/25mm:	30
Tensile strength N/25mm:	13
Total elongation:	450%
Temperature resistance:	from -30°C to +120°C
Temperature of use:	+13°C – +33°C



STORAGE



Protect the product from excessive low and high temperatures. Avoid direct exposure to sunlight. Store in dry places.



SHELF LIFE

12 months when stored in a dry place at 18°C - 21°C.



OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure its suitability for a specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specifications.