

TECHNICAL DATA SHEET PREFILL SPRAY

EAN code: 5907588400374 item no.: 001028 female
EAN code: 5907588403627 item no.: 0010281 PROFI female
EAN code: 5907588407830 item no.: 0010282 PROFI PLUS female



+ PROPERTIES

The refill spray is filled with gas and is ready for use after adding paint of the appropriate shade. The 400 ml can is capable of holding up to 100 ml of paint with viscosity up to 240s. (din4/20°C). Almost any type of paint can be used. It dilutes acrylic, alkyd and cellulose varnishes very well. Product capacity 1-2m² depending on the thickness of the layer. Drying time depends on the type of varnish used.

NOTE: the product is dedicated for one-component agents. Pass acrylic varnishes through a sieve.

METHOD OF USE

Thoroughly clean and degrease and then dry the areas to be covered with paint. Cover adherent surfaces with paper. Shake the container well for about 3 minutes before use. Hold the container at a distance of 15-20 cm from the surface to be covered. After use, turn the container over and spray until the valve is empty.

Important: after filling the can with thick paint, flush the valve with 10 ml of solvent in the same way as when filling with paint. Use the solvent according to the recipe of your mixing plant.

+ PHYSICAL PROPERTIES

Physical state:	aerosol
Temperature of use:	+15°C – +25°

STORAGE



Protect the product from excessive low and high temperatures. Avoid direct exposure to sunlight. Store in dry places.

SHelf LIFE

Two years from the production date placed on the package.

! SAFETY

See Safety data Sheet.

☰ OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure its suitability for a specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specifications.