



QUICK-DRYING PRIMING PAINT SPRAY

EAN code: 5907588407922 item no.: 0010210 white
EAN code: 5907588402545 item no.: 001020 beige
EAN code: 5907588410007 item no.: 001021 grey
EAN code: 5907588403641 item no.: 0010199 black



+ PROPERTIES

Quick-drying spray primer, perfect for surface preparation when painting car body parts. It has excellent anticorrosive and scratch-resistant properties, making it a very good foundation for various types of paint. Easy to work with, does not clog the sandpaper. Can be coated with acrylic, alkyd, cellulose and epoxy paints.

+ COLOUR

○ white ● beige ● grey ● black

+ METHOD OF USE

Thoroughly clean, degrease and then dry the surface. Before applying the primer, we recommend to matt the surface and to clean and degrease it again. Cover adjacent areas with masking materials. Shake the container well for about 3 minutes before use. When painting, keep the container at 15-20 cm distance from the substrate. After about 1 hour the surface can be varnished. After use, invert the container and spray until the valve is empty.

= SUBSTRATE

- **metal** - sand, blow and degrease with "BOLL silicone remover", and then apply another layer.

- **non-ferrous metals (zinc, aluminum, copper, etc.)** - grind, blow and degrease with "BOLL silicone remover", and then apply another layer.

- **reactive primer** - sand, blow, degrease with "BOLL silicone remover", and then apply another layer

- **epoxy primer** - can be used to isolate materials. After sanding, blow, degrease with "BOLL silicone remover", and then apply another layer.

- **two-component acrylic primer** – apply control powder or spray. After sanding with fine paper P800-P1200 dry or P400-P600 wet, blow, degrease with "BOLL silicone remover", and then apply another layer.

- **polyester putties** - sand, blow and degrease with "BOLL silicone remover", and then apply another layer.



APPLICATION



Thoroughly clean and roughen the surface



Thoroughly clean and degrease the surface



Mix thoroughly



Apply 2-3 layers from a distance of 15-20 cm



Flash off time between layers: 5 ÷ 10 minutes



After about 1 hour, the surface can be varnished



After use, invert the container and spray until the valve is empty



STORAGE CONDITIONS



Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.



SHELF LIFE

24 months from the production date placed on the package.



SAFETY

See Safety Data Sheet.



OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.