

TECHNICAL DATA SHEET

## QUICK-DRYING PRIMER PAINT SPRAY

**EAN code:** 5907588407922 item no.: 0010210 white

**EAN code:** 5907588402545 item no.: 001020 beige

**EAN code:** 5907588410007 item no.: 001021 grey

**EAN code:** 5907588403641 item no.: 0010199 black



### + PROPERTIES

The quick-drying primer paint is ideal for preparing the substrate in paint jobs on car body parts. It has excellent rust protection properties and is highly scratch resistant, making it a very good substrate before applying paint. Easy to work with, it does not cause sandpaper clogging. It can be coated with acrylic, alkyd, cellulose and epoxy paints.

### COLOUR



white



beige



grey



black

### = SURFACE

- metal** - sand, blow off and degrease with "BOLL Silicon remover", then apply another coat.
- non-ferrous metals (zinc, aluminium, cooper, etc.)** - prime, sand, blow off and degrease with "BOLL Silicon remover", then apply another coat.
- old primer coatings** - sand with P240 - P320 paper, blow off, degrease with "BOLL Silicon remover", and then apply another coat.
- epoxy primer** - can be used to isolate materials. After sanding, blow off, degrease with "BOLL Silicon remover", and then apply another coat.
- two-component acrylic primer** - sand, blow off, degrease with "BOLL Silicon remover", and then apply another coat.
- polyester putties** - sand, blow off and degrease with "BOLL Silicon remover", and then apply another coat.

## APPLICATION



Thoroughly clean and mat the surface



Thoroughly clean and degrease the surface with BOLL Silicon remover



Mix thoroughly



Apply 2-3 layers from a distance of 15-20 cm



Time between layers: 5 – 10 minutes



After about 1 hour, the surface can be coated with varnish



After use, turn the container over and spray until the valve is empty

## PHYSICAL PROPERTIES

Physical state:

aerosol

Temperature of use:

+18°C – +25°C

## STORAGE



Protect the product from excessive low and high temperatures. Avoid direct exposure to sunlight. Store in dry places.

## SHELF LIFE

Two years from the production date placed on the package.

## ! SAFETY

See Safety Data Sheet.

## ☰ OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure its suitability for a specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specifications.