

TECHNICAL DATA SHEET

## PRIMER FILLER SPRAY

**EAN code:** 5907588407953 item no.: 001053 black

**EAN code:** 5907588407946 item no.: 001052 grey

**EAN code:** 5907588407939 item no.: 001051 white



### + PROPERTIES

Quick-drying acrylic primer spray. The product offers excellent filling and anti-corrosive properties, making it ideal for surface preparation in painting and varnishing projects. It is specifically designed for leveling putty and old coatings, providing superb adhesion to a wide range of surfaces. Easy to sand, it can be coated with most available paints and varnishes.

### • COLOUR



white



grey



black

### = SURFACE

- **metal** - sand, blow off and degrease with "BOLL Silicon remover", and then apply another coat.
- **non-ferrous metals (zinc, aluminum, copper, etc.)** - prime, sand, blow off and degrease with "BOLL silicone remover", then apply another coat.
- **old paint coatings** - sand with P220 - P320, blow off, degrease with "BOLL Silicon remover", and then apply another coat.
- **epoxy primer** - can be used to isolate materials. After sanding, blow off, degrease with "BOLL Silicon remover" and then apply another coat.
- **two-component acrylic primer** - apply lacquer or powder control. After sanding, blow off, degrease with "BOLL Silicon remover" and then apply another coat.
- **polyester putty** - sand, blow off and degrease with "BOLL Silicon remover", and then apply another coat.

## APPLICATION



Thoroughly clean and sand the surface with P240 - P360



Thoroughly clean and degrease the surface with BOLL Silicon remover



Mix thoroughly



Apply 2 – 3 layers from a distance of 15 – 20 cm



Time between layers: 5 – 10 minutes



After about 1.5 hours, the surface can be coated with varnish



After use, turn the container over and spray until the valve is empty

## PHYSICAL PROPERTIES

Physical state:	aerosol
Temperature of use:	+15°C – +25°C

## STORAGE



Protect the product from excessive low and high temperatures. Avoid direct exposure to sunlight. Store in dry places.

## SHELF LIFE

Two years from the production date placed on the package.

## ! SAFETY

See Safety data Sheet.

## ☰ OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure its suitability for a specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specifications.