

TECHNICAL DATA SHEET

MASKING TAPE 60°C

EAN code: 5907588408851 item no.: 0040051 type 19mm/50m
EAN code: 5907588408875 item no.: 0040052 type 25mm/50m
EAN code: 5907588408899 item no.: 0040053 type 30mm/50m
EAN code: 5907588408912 item no.: 0040054 type 38mm/50m
EAN code: 5907588408936 item no.: 0040055 type 50mm/50m




+ PROPERTIES

High-quality masking tape used in painting work. It adheres well to various surfaces and does not leave marks after the drying process.

It comes in rolls of 50 m length and widths: 19, 25, 30, 38 and 50 mm

• COLOUR



white

☞ METHOD OF USE

The tape is designed for use in automotive and industrial painting. The surface to which the tape is to be applied should be dust-free and degreased.

+ PHYSICAL PROPERTIES

Description:	heat-resistant paper masking tape, saturated crepe paper
Binder:	natural rubber
Total thickness:	130 µm
Adhesion to steel N/25mm:	6,0
Tensile strength N/25mm:	85
Total elongation:	7%
Rolling ball tack test:	2 cm
Temperature of use:	+15°C – +35°C

STORAGE



Protect the product from excessive low and high temperatures. Avoid direct exposure to sunlight. Store in dry places.

SHELF LIFE

12 months when stored in a dry place at 18°C - 21°C.

OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure its suitability for a specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specifications.