

CLEAR COAT VHS 2:1

EAN code: 5907588409100 item no.: 001664

EAN code: 5907588409117 item no.: 001665 hardener STANDARD



+ PROPERTIES

Top-grade VHS clearcoat (Very High Solid). It has a very high scratch resistance and the highest gloss. The product has a very high performance due to the high content of solids. The varnish allows you to get any structure and copy OEM painting. Does not require the use of a thinner.







• COLOUR

clear

= SURFACE

Can be applied over most available solvent and waterborne basecoats.

↓ APPLICATION

	Mixing ratio:	by volume	by mass
	clear coat hardener STANDARD	2 1	100g 52g
	Viscosity: DIN 4 20°C 18 - 22 s		
	Mixture life hardener STANDARD 20°C 1,5 h		
	Nozzle 1,2 - 1,3 mm Pressure 1,2 - 2,5 bar Number of layers 2 layers		
	Evaporation time 5 - 10 min		
	Dust free Operating hardness Overall hardness	20°C STANDARD 30 min 12 h 36 h	60°C STANDARD 5 min 30 min + 2h/20°C 30 min + 24h/20°C



Short waves
max 90°C
8 - 12 min



STORAGE CONDITIONS



Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.



SHELF LIFE

24 months from the production date placed on the packaging.



SAFETY

See Safety Data Sheet.



OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.