


CLEAR COAT VHS 2:1

EAN code: 5907588409100 item no.: 001664







PROPERTIES

Top-grade VHS clearcoat (Very High Solid). It has a very high scratch resistance and the highest gloss. The product has a very high performance due to the high content of solids. The varnish allows you to get any structure and copy OEM painting. Does not require the use of a thinner.



COLOUR

clear



SURFACE

Can be applied over most available solvent and waterborne basecoats.



APPLICATION

Mixing ratio:	by volume	by mass
clear coat	2	100g
hardener STANDARD	1	52g

60°C



Viscosity: DIN 4 20°C 18 - 22 s



Mixture life

hardener STANDARD

20°C 1,5 h



Nozzle 1,2 - 1,3 mm Pressure 1,2 - 2,5 bar Number of layers 2 layers



Evaporation time 5 - 10 min



 $\begin{array}{ccc} & STANDARD & STANDARD \\ Dust free & 30 \min & 5 \min \\ Operating hardness & 12 h & 30 \min + 2h/20 ^{\circ}C \\ Overall hardness & 36 h & 30 \min + 24h/20 ^{\circ}C \end{array}$

20°C

CLEAR COAT VHS 2:1 Page - 1



Short waves max 90°C 8 - 12 min



STORAGE CONDITIONS







Protect the product from excessive heat and cold. Avoid direct exposure to sunlight. Store in a dry place.



24 months from the production date placed on the packaging.



SAFETY

See Safety Data Sheet.



OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure suitability for your specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specification.

CLEAR COAT VHS 2:1 Page - 2