

**LAKIER DO ZACISKÓW ŻŁOTY - BRAKE CALIPER PAINT****SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier:** LAKIER DO ZACISKÓW ŻŁOTY - BRAKE CALIPER PAINT**Other means of identification:**

Mixture identifier: contains: acetone, xylene - mixture of isomers.

**UFI:** AW23-90WU-300R-QNG1**1.2 Relevant identified uses of the substance or mixture and uses advised against:**

Relevant uses: Covering different surfaces with a spray.

Uses advised against: All uses not specified in this section or in section 7.3

**1.3 Details of the supplier of the safety data sheet:**

BOLL Wojciech Dalewski Spółka Jawna  
ul. Chemiczna 3  
65-713 Zielona Góra - Polska  
Phone: 68 451 99 99 - Fax: 68 451 99 00  
huszcza@boll.pl  
<https://www.boll.pl>

**1.4 Emergency telephone number:****SECTION 2: HAZARDS IDENTIFICATION****2.1 Classification of the substance or mixture:****CLP Regulation (EC) No 1272/2008:**

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aerosol 1: Flammable aerosols, Category 1, H222

Aerosol 1: Pressurised container: May burst if heated., H229

Eye Irrit. 2: Eye irritation, Category 2, H319

Skin Irrit. 2: Skin irritation, Category 2, H315

STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2 (Oral), H373

STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

**2.2 Label elements:****CLP Regulation (EC) No 1272/2008:****Danger****Hazard statements:**

Aerosol 1: H222 - Extremely flammable aerosol.

Aerosol 1: H229 - Pressurised container: May burst if heated.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Skin Irrit. 2: H315 - Causes skin irritation.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).

STOT SE 3: H336 - May cause drowsiness or dizziness.

**Precautionary statements:**

P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P271: Use only outdoors or in a well-ventilated area.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P337+P313: If eye irritation persists: Get medical advice/attention.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

**Substances that contribute to the classification**

acetone; Xylene

- CONTINUED ON NEXT PAGE -



## Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

## LAKIER DO ZACISKÓW ŻŁOTY - BRAKE CALIPER PAINT

## SECTION 2: HAZARDS IDENTIFICATION (continued)

**UFI:** AW23-90WU-300R-QNG1

The product packaging must include: tactile warning.

**2.3 Other hazards:**

Product does not meet PBT/vPvB criteria

Endocrine-disrupting properties: The product does not meet the criteria.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

**3.1 Substance:**

Non-applicable

**3.2 Mixture:****Chemical description:** active ingredient mixture with a propellant. Propellant: propane - butane**Components:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 68476-40-4 EC: 270-681-9 Index: 649-199-00-1 REACH: 01-2119486557-22-XXXX	<b>Hydrocarbons, C3-4, &lt; 0.1 % EC 203-450-8<sup>(1)</sup></b> Regulation 1272/2008 Flam. Gas 1A: H220; Press. Gas: H280 - Danger	Self-classified 25 - <45 %
CAS: 67-64-1 EC: 200-662-2 Index: 606-001-00-8 REACH: 01-2119471330-49-XXXX	<b>acetone<sup>(2)</sup></b> Regulation 1272/2008 Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	ATP CLP00 20 - <30 %
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32-XXXX	<b>Xylene<sup>(2)</sup></b> Regulation 1272/2008 Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	Self-classified 15 - <19 %
CAS: 100-41-4 EC: 202-849-4 Index: 601-023-00-4 REACH: 01-2119489370-35-XXXX	<b>Ethylbenzene<sup>(2)</sup></b> Regulation 1272/2008 Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger	ATP ATP06 <5 %
CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29-XXXX	<b>N-butyl acetate<sup>(2)</sup></b> Regulation 1272/2008 Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning	ATP CLP00 <5 %

<sup>(1)</sup> Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2020/878<sup>(2)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute toxicity		Genus
	LD50 oral	Not relevant	
Xylene	LD50 dermal	1100 mg/kg	Rat
CAS: 1330-20-7	LC50 inhalation	11 mg/L (ATEi)	
EC: 215-535-7			

## SECTION 4: FIRST AID MEASURES

**4.1 Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

**By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

- CONTINUED ON NEXT PAGE -

**LAKIER DO ZACISKÓW ŻŁOTY - BRAKE CALIPER PAINT****SECTION 4: FIRST AID MEASURES (continued)****By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

**By ingestion/aspiration:**

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

**4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of any immediate medical attention and special treatment needed:**

Not available

**SECTION 5: FIREFIGHTING MEASURES****5.1 Extinguishing media:****Suitable extinguishing media:**

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

**Unsuitable extinguishing media:**

Water jet

**5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

**Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

**SECTION 6: ACCIDENTAL RELEASE MEASURES****6.1 Personal precautions, protective equipment and emergency procedures:****For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

**For emergency responders:**

Wear protective equipment. Keep unprotected persons away. See section 8.

**6.2 Environmental precautions:**

It is recommended to avoid environmental spillage of both the product and its container.

**6.3 Methods and material for containment and cleaning up:**

- CONTINUED ON NEXT PAGE -

**LAKIER DO ZACISKÓW ŻŁOTY - BRAKE CALIPER PAINT****SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)**

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

**6.4 Reference to other sections:**

See sections 8 and 13.

**SECTION 7: HANDLING AND STORAGE****7.1 Precautions for safe handling:**

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

**7.2 Conditions for safe storage, including any incompatibilities:**

A.- Technical measures for storage

Minimum Temp.: 5 °C  
Maximum Temp.: 35 °C  
Maximum time: 24 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
	IOELV (8h)	500 ppm	1210 mg/m <sup>3</sup>
acetone CAS: 67-64-1 EC: 200-662-2	IOELV (STEL)		
Xylene <sup>(1)</sup> CAS: 1330-20-7 EC: 215-535-7	IOELV (8h)	50 ppm	221 mg/m <sup>3</sup>
	IOELV (STEL)	100 ppm	442 mg/m <sup>3</sup>
Ethylbenzene <sup>(1)</sup> CAS: 100-41-4 EC: 202-849-4	IOELV (8h)	100 ppm	442 mg/m <sup>3</sup>
	IOELV (STEL)	200 ppm	884 mg/m <sup>3</sup>
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	IOELV (8h)	50 ppm	241 mg/m <sup>3</sup>
	IOELV (STEL)	150 ppm	723 mg/m <sup>3</sup>

<sup>(1)</sup> Likely absorption through the skin

**DNEL (Workers):**

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**LAKIER DO ZACISKÓW ŻŁOTY - BRAKE CALIPER PAINT**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Hydrocarbons, C3-4, < 0.1 % EC 203-450-8 CAS: 68476-40-4 EC: 270-681-9	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	23,4 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	Not relevant	Not relevant
acetone CAS: 67-64-1 EC: 200-662-2	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	186 mg/kg	Not relevant
	Inhalation	Not relevant	2420 mg/m <sup>3</sup>	1210 mg/m <sup>3</sup>	Not relevant
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	212 mg/kg	Not relevant
	Inhalation	442 mg/m <sup>3</sup>	442 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	180 mg/kg	Not relevant
	Inhalation	Not relevant	293 mg/m <sup>3</sup>	77 mg/m <sup>3</sup>	Not relevant
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	11 mg/kg	Not relevant	11 mg/kg	Not relevant
	Inhalation	600 mg/m <sup>3</sup>	600 mg/m <sup>3</sup>	300 mg/m <sup>3</sup>	300 mg/m <sup>3</sup>

**DNEL (General population):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
acetone CAS: 67-64-1 EC: 200-662-2	Oral	Not relevant	Not relevant	62 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	62 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	200 mg/m <sup>3</sup>	Not relevant
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Not relevant	Not relevant	12,5 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	125 mg/kg	Not relevant
	Inhalation	260 mg/m <sup>3</sup>	260 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Oral	Not relevant	Not relevant	1,6 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	Not relevant	15 mg/m <sup>3</sup>	Not relevant
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	2 mg/kg	Not relevant	2 mg/kg	Not relevant
	Dermal	6 mg/kg	Not relevant	6 mg/kg	Not relevant
	Inhalation	300 mg/m <sup>3</sup>	300 mg/m <sup>3</sup>	35,7 mg/m <sup>3</sup>	35,7 mg/m <sup>3</sup>

**PNEC:**

Identification				
acetone CAS: 67-64-1 EC: 200-662-2	STP	100 mg/L	Fresh water	10,6 mg/L
	Soil	29,5 mg/kg	Marine water	1,06 mg/L
	Intermittent	21 mg/L	Sediment (Fresh water)	30,4 mg/kg
	Oral	Not relevant	Sediment (Marine water)	3,04 mg/kg
Xylene CAS: 1330-20-7 EC: 215-535-7	STP	6,58 mg/L	Fresh water	0,327 mg/L
	Soil	2,31 mg/kg	Marine water	0,327 mg/L
	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Not relevant	Sediment (Marine water)	12,46 mg/kg
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	STP	9,6 mg/L	Fresh water	0,1 mg/L
	Soil	2,68 mg/kg	Marine water	0,01 mg/L
	Intermittent	0,1 mg/L	Sediment (Fresh water)	13,7 mg/kg
	Oral	0,02 g/kg	Sediment (Marine water)	1,37 mg/kg
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	STP	35,6 mg/L	Fresh water	0,18 mg/L
	Soil	0,09 mg/kg	Marine water	0,018 mg/L
	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0,098 mg/kg

**8.2 Exposure controls:**

A.- Individual protection measures, such as personal protective equipment



- CONTINUED ON NEXT PAGE -

**LAKIER DO ZACISKÓW ŻŁOTY - BRAKE CALIPER PAINT**



**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

**B.- Respiratory protection**



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases, vapours and particles	 CAT III	EN 149:2001+A1:2009 EN 405:2002+A1:2010 EN ISO 136:1998	Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected.

**C.- Specific protection for the hands**





Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)	 CAT III	EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



**D.- Eye and face protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.	 CAT II	EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

**E.- Body protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Antistatic and fireproof protective clothing	 CAT III	EN 1149-1:2006 EN 1149-2:1997 EN 1149-3:2004 EN 168:2002 EN ISO 14116:2015 EN 1149-5:2018	Limited protection against flames.
 Mandatory foot protection	Safety footwear with antistatic and heat resistant properties	 CAT III	EN ISO 13287:2020 EN ISO 20345:2011	Replace boots at any sign of deterioration.

**F.- Additional emergency measures**

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

**Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

**Volatile organic compounds:**

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	55,1 % weight
V.O.C. density at 20 °C:	680 kg/m <sup>3</sup> (680 g/L)
Average carbon number:	5,22

- CONTINUED ON NEXT PAGE -

**LAKIER DO ZACISKÓW ŻŁOTY - BRAKE CALIPER PAINT****SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Average molecular weight: 80,43 g/mol

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

V.O.C. density at 20 °C: 680 kg/m<sup>3</sup> (680 g/L)

EU limit for the product (Cat. B.E): 840 g/L (2010)

Components: Not relevant

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES****9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

**Appearance:**

Physical state at 20 °C: Aerosol

Appearance: Fluid

Colour: According to the markings on the package

Odour: Characteristic

Odour threshold: Not available \*

**Volatility:**

Boiling point at atmospheric pressure: -42 - 142 °C (Propellant)

Vapour pressure at 20 °C: Not available \*

Vapour pressure at 50 °C: Not available \*

Evaporation rate at 20 °C: Not available \*

**Product description:**Density at 20 °C: 700 kg/m<sup>3</sup>

Relative density at 20 °C: 0,7

Dynamic viscosity at 20 °C: Not available \*

Kinematic viscosity at 20 °C: Not available \*

Kinematic viscosity at 40 °C: <20,5 mm<sup>2</sup>/s

Concentration: Not available \*

pH: Not available \*

Vapour density at 20 °C: Not available \*

Partition coefficient n-octanol/water 20 °C: Not available \*

Solubility in water at 20 °C: Not available \*

Solubility properties: Soluble

Decomposition temperature: Not available \*

Melting point/freezing point: Not available \*

Recipient pressure: Not available \*

**Flammability:**

Flash Point: -105 °C (Propellant)

Flammability (solid, gas): Not available \*

Autoignition temperature: &gt;287 °C (Propellant)

Lower flammability limit: 1,9 % Volume

Upper flammability limit: 9,6 % Volume

**Particle characteristics:**

Median equivalent diameter: Non-applicable

\*Not available due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

**LAKIER DO ZACISKÓW ŻŁOTY - BRAKE CALIPER PAINT****SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)****9.2 Other information:****Information with regard to physical hazard classes:**

Explosive properties:	Not available *
Oxidising properties:	Not available *
Corrosive to metals:	Not available *
Heat of combustion:	Not available *
Aerosols-total percentage (by mass) of flammable components:	Not available *

**Other safety characteristics:**

Surface tension at 20 °C:	Not available *
Refraction index:	Not available *

\*Not available due to the nature of the product, not providing information property of its hazards.

**SECTION 10: STABILITY AND REACTIVITY****10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

**10.2 Chemical stability:**

Chemically stable under the indicated conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

**10.5 Incompatible materials:**

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

**10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

**SECTION 11: TOXICOLOGICAL INFORMATION****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:**

The experimental information related to the toxicological properties of the product itself is not available

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

**A- Ingestion (acute effect):**

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

**B- Inhalation (acute effect):**

- CONTINUED ON NEXT PAGE -



**LAKIER DO ZACISKÓW ŻŁOTY - BRAKE CALIPER PAINT****SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Produces skin inflammation.
  - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.  
IARC: Xylene (3); Ethylbenzene (2B)
  - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
  - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
  - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- G- Specific target organ toxicity (STOT)-repeated exposure:
  - Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
  - Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

**Other information:**

Not relevant

**Specific toxicology information on the substances:**

Identification	Acute toxicity		Genus
Hydrocarbons, C3-4, < 0.1 % EC 203-450-8 CAS: 68476-40-4 EC: 270-681-9	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation	>5 mg/L	
acetone CAS: 67-64-1 EC: 200-662-2	LD50 oral	5800 mg/kg	Rat
	LD50 dermal	7426 mg/kg	Rabbit
	LC50 inhalation	76 mg/L (4 h)	Rat
Xylene CAS: 1330-20-7 EC: 215-535-7	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg (ATEi)	Rat
	LC50 inhalation	11 mg/L (ATEi)	
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LD50 oral	3500 mg/kg	Rat
	LD50 dermal	15354 mg/kg	Rabbit
	LC50 inhalation	17,2 mg/L (4 h)	Rat
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LD50 oral	12789 mg/kg	Rat
	LD50 dermal	14112 mg/kg	Rabbit
	LC50 inhalation	23,4 mg/L (4 h)	Rat

**11.2 Information on other hazards:**

- CONTINUED ON NEXT PAGE -



## Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**LAKIER DO ZACISKÓW ŻŁOTY - BRAKE CALIPER PAINT****SECTION 11: TOXICOLOGICAL INFORMATION (continued)****Endocrine disrupting properties**

Endocrine-disrupting properties: The product does not meet the criteria.

**Other information**

Not relevant

**SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

**12.1 Toxicity:****Acute toxicity:**

Identification	Concentration	Species	Genus
acetone CAS: 67-64-1 EC: 200-662-2	LC50 5540 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50 8800 mg/L (48 h)	Daphnia pulex	Crustacean
	EC50 3400 mg/L (48 h)	Chlorella pyrenoidosa	Algae
Xylene CAS: 1330-20-7 EC: 215-535-7	LC50 >10 - 100 mg/L (96 h)		Fish
	EC50 >10 - 100 mg/L (48 h)		Crustacean
	EC50 >10 - 100 mg/L (72 h)		Algae
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	LC50 42,3 mg/L (96 h)	Pimephales promelas	Fish
	EC50 75 mg/L (48 h)	Daphnia magna	Crustacean
	EC50 63 mg/L (3 h)	Chlorella vulgaris	Algae
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LC50 Not relevant		
	EC50 Not relevant		
	EC50 675 mg/L (72 h)	Scenedesmus subspicatus	Algae

**Chronic toxicity:**

Identification	Concentration	Species	Genus
acetone CAS: 67-64-1 EC: 200-662-2	NOEC Not relevant		
	NOEC 2212 mg/L	Daphnia magna	Crustacean
Xylene CAS: 1330-20-7 EC: 215-535-7	NOEC 1,3 mg/L	Oncorhynchus mykiss	Fish
	NOEC 1,17 mg/L	Ceriodaphnia dubia	Crustacean
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	NOEC Not relevant		
	NOEC 0,96 mg/L	Ceriodaphnia dubia	Crustacean
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	NOEC Not relevant		
	NOEC 23,2 mg/L	Daphnia magna	Crustacean

**12.2 Persistence and degradability:****Substance-specific information:**

Identification	Degradability		Biodegradability	
acetone CAS: 67-64-1 EC: 200-662-2	BOD5	Not relevant	Concentration	100 mg/L
	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	96 %
Xylene CAS: 1330-20-7 EC: 215-535-7	BOD5	Not relevant	Concentration	Not relevant
	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	88 %
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	BOD5	Not relevant	Concentration	100 mg/L
	COD	Not relevant	Period	14 days
	BOD5/COD	Not relevant	% Biodegradable	90 %
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	BOD5	Not relevant	Concentration	Not relevant
	COD	Not relevant	Period	5 days
	BOD5/COD	Not relevant	% Biodegradable	84 %

- CONTINUED ON NEXT PAGE -

**LAKIER DO ZACISKÓW ŻŁOTY - BRAKE CALIPER PAINT****SECTION 12: ECOLOGICAL INFORMATION (continued)****12.3 Bioaccumulative potential:****Substance-specific information:**

Identification	Bioaccumulation potential	
acetone CAS: 67-64-1 EC: 200-662-2	BCF	1
	Pow Log	-0.24
	Potential	Low
Xylene CAS: 1330-20-7 EC: 215-535-7	BCF	9
	Pow Log	2.77
	Potential	Low
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	BCF	1
	Pow Log	3.15
	Potential	Low
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	BCF	4
	Pow Log	1.78
	Potential	Low

**12.4 Mobility in soil:**

Identification	Absorption/desorption		Volatility	
acetone CAS: 67-64-1 EC: 200-662-2	Koc	1	Henry	2,93 Pa·m <sup>3</sup> /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2,304E-2 N/m (25 °C)	Moist soil	Yes
Xylene CAS: 1330-20-7 EC: 215-535-7	Koc	202	Henry	524,86 Pa·m <sup>3</sup> /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Not relevant	Moist soil	Yes
Ethylbenzene CAS: 100-41-4 EC: 202-849-4	Koc	520	Henry	798,44 Pa·m <sup>3</sup> /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	2,859E-2 N/m (25 °C)	Moist soil	Yes
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Koc	Not relevant	Henry	Not relevant
	Conclusion	Not relevant	Dry soil	Not relevant
	Surface tension	2,478E-2 N/m (25 °C)	Moist soil	Not relevant

**12.5 Results of PBT and vPvB assessment:**

Product does not meet PBT/vPvB criteria

**12.6 Endocrine disrupting properties:**

Endocrine-disrupting properties: The product does not meet the criteria.

**12.7 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS****13.1 Waste treatment methods:**

Code	Description	Waste class (Regulation (EU) No 1357/2014)
16 05 04*	gases in pressure containers (including halons) containing hazardous substances	Hazardous

**Type of waste (Regulation (EU) No 1357/2014):**

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP4 Irritant — skin irritation and eye damage

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

- CONTINUED ON NEXT PAGE -

**LAKIER DO ZACISKÓW ŻŁOTY - BRAKE CALIPER PAINT**

**SECTION 13: DISPOSAL CONSIDERATIONS (continued)**

**Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

**SECTION 14: TRANSPORT INFORMATION**

**Transport of dangerous goods by land:**

With regard to ADR 2023 and RID 2023:



- 14.1 UN number or ID number:** UN1950
- 14.2 UN proper shipping name:** AEROSOLS
- 14.3 Transport hazard class(es):** 2  
Labels: 2.1
- 14.4 Packing group:** N/A
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**  
Special regulations: 190, 327, 344, 625  
Tunnel restriction code: D  
Physico-Chemical properties: see section 9  
Limited quantities: 1 L
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

**Transport of dangerous goods by sea:**

With regard to IMDG 41-22:



- 14.1 UN number or ID number:** UN1950
- 14.2 UN proper shipping name:** AEROSOLS
- 14.3 Transport hazard class(es):** 2  
Labels: 2.1
- 14.4 Packing group:** N/A
- 14.5 Marine pollutant:** No
- 14.6 Special precautions for user**  
Special regulations: 63, 959, 190, 277, 327, 344  
EmS Codes: F-D, S-U  
Physico-Chemical properties: see section 9  
Limited quantities: 1 L  
Segregation group: Not relevant
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2024:



- 14.1 UN number or ID number:** UN1950
- 14.2 UN proper shipping name:** AEROSOLS
- 14.3 Transport hazard class(es):** 2  
Labels: 2.1
- 14.4 Packing group:** N/A
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**  
Physico-Chemical properties: see section 9
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

- CONTINUED ON NEXT PAGE -

**LAKIER DO ZACISKÓW ŻŁOTY - BRAKE CALIPER PAINT****SECTION 15: REGULATORY INFORMATION****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

- Article 95, REGULATION (EU) No 528/2012: Not relevant
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Not relevant
- Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

**Seveso III:**

Section	Description	Lower-tier requirements	Upper-tier requirements
P3a	FLAMMABLE AEROSOLS	150	500

**Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):**

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors: Contains acetone. Product under the provisions of Article 9. However, products that contain explosives precursors only to such a small extent and in such complex mixtures that the extraction of the explosives precursors is technically extremely difficult should be excluded from the scope of this Regulation.

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

**Other legislation:**

The product could be affected by sectorial legislation

**15.2 Chemical safety assessment:**

The supplier has not carried out evaluation of chemical safety.

**SECTION 16: OTHER INFORMATION****Legislation related to safety data sheets:**

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

**Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:**

Not relevant

**Texts of the legislative phrases mentioned in section 2:**

H222: Extremely flammable aerosol.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H373: May cause damage to organs through prolonged or repeated exposure (Oral).

H229: Pressurised container: May burst if heated.

**Texts of the legislative phrases mentioned in section 3:**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

**CLP Regulation (EC) No 1272/2008:**

- CONTINUED ON NEXT PAGE -

**LAKIER DO ZACISKÓW ŻŁOTY - BRAKE CALIPER PAINT****SECTION 16: OTHER INFORMATION (continued)**

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.  
Acute Tox. 4: H332 - Harmful if inhaled.  
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.  
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.  
Eye Irrit. 2: H319 - Causes serious eye irritation.  
Flam. Gas 1A: H220 - Extremely flammable gas.  
Flam. Liq. 2: H225 - Highly flammable liquid and vapour.  
Flam. Liq. 3: H226 - Flammable liquid and vapour.  
Press. Gas: H280 - Contains gas under pressure, may explode if heated.  
Skin Irrit. 2: H315 - Causes skin irritation.  
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).  
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.  
STOT SE 3: H335 - May cause respiratory irritation.  
STOT SE 3: H336 - May cause drowsiness or dizziness.

**Classification procedure:**

Aerosol 1: Calculation method  
Skin Irrit. 2: Calculation method  
Eye Irrit. 2: Calculation method  
STOT SE 3: Calculation method  
STOT RE 2: Calculation method  
Aerosol 1: Calculation method

**Advice related to training:**

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

**Principal bibliographical sources:**

<http://echa.europa.eu>  
<http://eur-lex.europa.eu>

**Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road  
IMDG: International maritime dangerous goods code  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organisation  
COD: Chemical Oxygen Demand  
BOD5: 5day biochemical oxygen demand  
BCF: Bioconcentration factor  
LD50: Lethal Dose 50  
LC50: Lethal Concentration 50  
EC50: Effective concentration 50  
LogPOW: Octanolwater partition coefficient  
Koc: Partition coefficient of organic carbon  
UFI: unique formula identifier  
IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -