

TECHNICAL DATA SHEET

ACRYLIC LACQUER RALLY SPRAY



EAN code: 5907588440011 item no.: 001011 black matt

EAN code: 5907588420006 item no.: 001012 black glossy

EAN code: 5907588404785 item no.: 0010126 white matt


EAN code: 5907588404792 item no.: 0010127 white glossy


EAN code: 5907588409360 item no.: 0010123 silver


+ PROPERTIES

Acrylic rally lacquer is a fast-drying paint characterized by good adhesion, for interior and exterior use. It is ideal for painting metal, wood, plastic, plaster, brick and paper. It can be used for touching up cars, furniture, for hobby purposes, etc. Creates an attractive, modern and durable layer with high flexibility.

COLOUR

 white matt/glossy

 silver

 black matt/glossy

APPLICATION



Thoroughly clean and mat the surface



Thoroughly clean and degrease the surface with BOLL Silicon remover



Mix thoroughly



Apply 2 – 3 layers from a distance of 15 – 20 cm



Time between layers: 5 – 10 minutes



Drying time 1 hour at 20°C



After use, turn the container over and spray until the valve is empty



PHYSICAL PROPERTIES

Physical state: aerosol
Temperature of use: +18°C – +25°C



STORAGE



Protect the product from excessive low and high temperatures. Avoid direct exposure to sunlight. Store in dry places.



SHELF LIFE

Two years from the date placed on the package.



SAFETY

See Safety Data Sheet.



OTHER INFORMATION

All technical data are approximate values. We advise you to test the material to ensure its suitability for a specific application. The producer reserves the right to improve the product and change the technical conditions with the possibility of making changes inside the specifications.